




## GPVWB Micro Capsule Filters

Hydrophobic PVDF Membrane

*GPVWB Micro Capsule filters are part of Critical Process Filtration's economical, general service product line that can be used to lower the total cost of filtration from simple to the most complex applications. Produced using the same quality materials and manufacturing excellence as our other product lines, you can be assured of their performance, dependability and scalability. While general service filters are not integrity tested or validated for retention, these highly efficient filters remove large amounts of contaminants early in the process to reduce the load on your expensive downstream filters. They are also useful as stand-alone clarifying or particle removal filters in less critical applications.*

GPVWB Micro Capsule filters consist of a single layer, hydrophobic, high capacity Polyvinylidene fluoride (PVDF) membrane. These filters are used for particle removal in non-aqueous liquids and for air/gas applications. Pore sizes range from 0.22 to 1.0  $\mu\text{m}$ . GPVWB Micro Capsule filters deliver high flow and throughput with the broad chemical compatibility of a fluoropolymer.

Critical Process provides unrivaled delivery times, technical consulting before purchasing, and very competitively priced high-performance products. Our comprehensive testing & analysis and validation services support your team whenever they need it. Your process experts partnering with our filtration experts is how we deliver your company's solution right the first time.



GPVWB Micro Capsule filters are recommended for:

- Compressed Air
- Non-Aqueous Solutions
- Compatible Solvents
- Tank Vents
- Acids and Bases

Fine Particle Removal

Tank Vent & Process Gas



### MICRO CAPSULES – Nominal Dimensions

Body Length: 1.9 in. (4.8 cm)

Overall Length: 2.8 to 3.8 in. (7.1 to 9.7 cm)

Outside Diameter: 2.6 in. (6.6 cm)

## Maximum Operating Parameters

	MICRO CAPSULES
<b>Liquid Operational Pressure</b>	80 psi at 68 °F (5.52 bard at 20 °C)
<b>Gases Operational Pressure</b>	60 psi at 68 °F (4.14 bar at 20 °C)
<b>Operating Temperature (water)</b>	110 °F at 30 psid (43 °C at 2.07 bard)
<b>Forward Differential Pressure</b>	Liquid - 80 psid at 68 °F (5.52 bard at 20 °C) Gas - 60 psi at 68 °F (4.14 bar at 20 °C)
<b>Reverse Differential Pressure</b>	50 psid at 68 °F (3.45 bard at 20 °C)
<b>Recommended Changeout Pressure</b>	35 psid (2.41 bard)

## Sanitization & Sterilization

<b>Autoclave</b>	250 °F (121 °C), 30 min, 5+ cycles
<b>Chemical Sanitization</b>	Performed using industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

### Extractables

GPVWB Micro Capsule filters typically exhibit low levels of non-volatile residues.

### Non-Fiber Releasing

The GPVWB Micro Capsule filters comply with Title 21 CFR sections 210.3 (b)(6) and 211.72, for non-fiber releasing filters.

### FDA and EC Compliance

Materials meet the requirements listed by the FDA as appropriate for use in articles intended for repeated food contact as specified in Title 21 CFR sections 174.5, 177.1500, 177.1520, 177.1630, 177.2440, and 177.2600 as applicable. All materials used to make the filters are listed in European Commission Regulation EU/10/2011, Annex 1.

### Filtration Area (Nominal)


Area	0.569 ft <sup>2</sup>
	529 cm <sup>2</sup>

### Construction Materials


<b>Filtration Media</b>	Hydrophobic High Capacity Polyvinylidene Fluoride (PVDF) Membrane
<b>Media Support</b>	Polypropylene
<b>End Caps, Center Core, Outer Support Cage, Micro Capsule Housing</b>	Polypropylene
<b>Sealing Method</b>	Thermal Bonding
<b>O-Rings/Gaskets Cartridges only</b>	Buna, Viton® (or FKM), EPDM, Silicone, FEP Encapsulated Silicone, FEP Encapsulated Viton (or FKM)

## Flow Rates for GPVWB Micro Capsules by Pore Size

### Water



### Air




Flow rates for Cartridge filters are per 10-inch length. The test fluid is water or compressed air at ambient temperature.

## GPVWB Micro Capsule Filters Ordering Information

All Critical Process filters are configurable to meet customer specifications. Fill in the corresponding codes in the boxes below to build your Part Number.

To consult with one of our technical team members, request a quote or place an order: call (603) 880-4420 or [contact us here](#).

### Micro Capsule Filters



\*When choosing the Sanitary Inlet/Outlet, the Luer Lock or bleed valve option is required for the Vent Port

\*\* O-Ring is only available on Bleed Valve



One Chestnut Street  
Nashua, NH 03060  
603.880.4420  
FAX: 603.880.4536

CriticalProcess.com

The information contained herein is subject to change without notice. The Critical Process Filtration logo is a trademark of Critical Process Filtration, Inc. Viton is a trademark of DuPont Performance Elastomers L.L.C.  
© 2025 Critical Process Filtration, Inc. • All Rights Reserved

Data Sheet GPVW Micro BDS Rev -